DX SERIES

►ALUMINUM COIL
►DEDICATED HORIZONTAL

DX SERIES: DIMENSIONAL DATA (In.)									
COIL MODELS	Dry Coil Static Pressure Drop (in. w.c.) @ CFM								
	400	600	800	1000	1200	1400	1600	1800	2000
DX24A3	0.130	0.252	0.459	-	-	-	-	-	-
DX24A4	0.179	0.361	0.552	-	-	-	-	-	-
DX24B3	0.093	0.179	0.337	0.520	-	-	-	-	-
DX24B4	0.130	0.264	0.459	-	-	-	-	-	-
DX24E2	0.028	0.057	0.106	0.154	0.227	0.313	0.410	0.508	-
DX24E3	0.033	0.106	0.179	0.252	0.374	0.495	-	-	-
DX24E4	0.057	0.142	0.240	0.361	0.508	-	-	-	-
DX30A3	0.093	0.179	0.337	0.520	-	-	-	-	-
DX30A4	0.130	0.264	0.459	-	-	-	-	-	-
DX30E3	0.033	0.093	0.167	0.227	0.337	0.459	0.581	-	-
DX30E4	0.057	0.130	0.227	0.325	0.459	-	-	-	-
DX36A3	0.093	0.179	0.337	0.520	-	-	-	-	-
DX36A4	0.130	0.264	0.459	-	-	-	-	-	-
DX36B3	0.045	0.130	0.203	0.313	0.459	-	-	-	-
DX36B4	0.081	0.179	0.288	0.447	-	-	-	-	-
DX36C3	0.069	0.154	0.252	0.398	0.568	-	-	-	-
DX36C4	0.106	0.215	0.361	0.544	-	-	-	-	-
DX36D3	0.022	0.045	0.106	0.154	0.203	0.276	0.361	0.459	0.556
DX36D4	0.041	0.081	0.142	0.215	0.288	0.386	0.495	-	-
DX36E3	0.035	0.069	0.130	0.179	0.264	0.361	0.471	0.581	-
DX36E4	0.045	0.106	0.179	0.252	0.374	0.495	-	-	-
DX36F3	0.033	0.093	0.167	0.227	0.337	0.459	0.581	-	-
DX36F4	0.057	0.130	0.227	0.325	0.459	-	-	-	-
DX42C3	0.028	0.057	0.118	0.179	0.240	0.325	0.422	0.520	-
DX42C4	0.033	0.093	0.167	0.240	0.337	0.447	0.581	-	-
DX42D3	0.028	0.057	0.106	0.167	0.215	0.288	0.386	0.483	0.581
DX42D4	0.041	0.081	0.154	0.227	0.301	0.410	0.520	-	-
DX48A3	0.033	0.106	0.179	0.252	0.374	0.495	-	-	-
DX48A4	0.057	0.142	0.240	0.361	0.508	-	-	-	-
DX48B3	0.041	0.081	0.142	0.203	0.288	0.398	0.508	-	-
DX48B4	0.045	0.118	0.203	0.288	0.410	0.544	-	-	-
DX48C3	0.035	0.069	0.130	0.179	0.264	0.361	0.471	0.581	-
DX48C4	0.045	0.106	0.179	0.252	0.374	0.495	-	-	-
DX48D3	0.022	0.045	0.106	0.154	0.203	0.276	0.361	0.459	0.556
DX48D4	0.041	0.081	0.142	0.215	0.288	0.386	0.495	-	-
DX60A3	0.028	0.057	0.118	0.179	0.240	0.325	0.422	0.520	-
DX60A4	0.033	0.093	0.167	0.240	0.337	0.447	0.581	-	-
DX60B3	0.022	0.045	0.106	0.154	0.203	0.276	0.361	0.459	0.556
DX60B4	0.041	0.081	0.142	0.215	0.288	0.386	0.495	-	-
DX60C3	0.014	0.028	0.057	0.093	0.130	0.167	0.203	0.264	0.325
DX60C4	0.016	0.033	0.081	0.130	0.179	0.227	0.288	0.361	0.447
DX60D3	0.011	0.022	0.045	0.093	0.130	0.167	0.203	0.252	0.313
DX60D4	0.016	0.033	0.081	0.130	0.179	0.227	0.288	0.361	0.434
DX60E3	0.011	0.022	0.045	0.069	0.106	0.142	0.191	0.215	0.276
DX60E4	0.016	0.033	0.069	0.106	0.154	0.203	0.252	0.313	0.374
DX60F3	0.022	0.045	0.093	0.154	0.191	0.264	0.349	0.434	0.532
DX60F4	0.041	0.081	0.142	0.203	0.276	0.374	0.483	0.593	-

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

DX SERIES

►ALUMINUM COIL
►DEDICATED HORIZONTAL

DX SERIES: DIMENSIONAL DATA (In.)									
COIL MODELS	Wet Coil Static Pressure Drop (in. w.c.) @ CFM								
	400	600	800	1000	1200	1400	1600	1800	2000
DX24A3	0.153	0.299	0.547	-	-	-	-	-	-
DX24A4	0.211	0.430	-	-	-	-	-	-	-
DX24B3	0.109	0.211	0.401	0.620	-	-	-	-	-
DX24B4	0.153	0.313	0.547	-	-	-	-	-	-
DX24E2	0.031	0.065	0.123	0.182	0.269	0.372	0.489	0.605	-
DX24E3	0.036	0.123	0.211	0.299	0.445	0.591	-	-	-
DX24E4	0.065	0.167	0.284	0.430	0.605	-	-	-	-
DX30A3	0.109	0.211	0.401	0.620	-	-	-	-	-
DX30A4	0.153	0.313	0.547	-	-	-	-	-	-
DX30E3	0.037	0.113	0.203	0.279	0.415	0.567	0.718	-	-
DX30E4	0.067	0.158	0.279	0.400	0.567	-	-	-	-
DX36A3	0.109	0.211	0.401	0.620	-	-	-	-	-
DX36A4	0.153	0.313	0.547	-	-	-	-	-	-
DX36B3	0.052	0.158	0.249	0.385	0.567	-	-	-	-
DX36B4	0.098	0.219	0.355	0.552	-	-	-	-	-
DX36C3	0.082	0.188	0.309	0.491	0.703	-	-	-	-
DX36C4	0.128	0.264	0.446	0.673	-	-	-	-	-
DX36D3	0.023	0.049	0.120	0.177	0.234	0.319	0.418	0.532	0.646
DX36D4	0.044	0.092	0.163	0.248	0.333	0.447	0.575	-	-
DX36E3	0.039	0.082	0.158	0.219	0.325	0.446	0.582	0.718	-
DX36E4	0.052	0.128	0.219	0.309	0.461	0.612	-	-	-
DX36F3	0.037	0.113	0.203	0.279	0.415	0.567	0.718	-	-
DX36F4	0.067	0.158	0.279	0.400	0.567	-	-	-	-
DX42C3	0.032	0.067	0.143	0.219	0.294	0.400	0.521	0.642	-
DX42C4	0.037	0.113	0.203	0.294	0.415	0.552	0.718	-	-
DX42D3	0.032	0.067	0.128	0.203	0.264	0.355	0.476	0.597	0.718
DX42D4	0.047	0.098	0.188	0.279	0.370	0.506	0.642	-	-
DX48A3	0.037	0.128	0.219	0.309	0.461	0.612	-	-	-
DX48A4	0.067	0.173	0.294	0.446	0.627	-	-	-	-
DX48B3	0.047	0.098	0.173	0.249	0.355	0.491	0.627	-	-
DX48B4	0.052	0.143	0.249	0.355	0.506	0.673	-	-	-
DX48C3	0.039	0.082	0.158	0.219	0.325	0.446	0.582	0.718	-
DX48C4	0.052	0.128	0.219	0.309	0.461	0.612	-	-	-
DX48D3	0.023	0.049	0.120	0.177	0.234	0.319	0.418	0.532	0.646
DX48D4	0.044	0.092	0.163	0.248	0.333	0.447	0.575	-	-
DX60A3	0.032	0.067	0.143	0.219	0.294	0.400	0.521	0.642	-
DX60A4	0.037	0.113	0.203	0.294	0.415	0.552	0.718	-	-
DX60B3	0.023	0.049	0.120	0.177	0.234	0.319	0.418	0.532	0.646
DX60B4	0.044	0.092	0.163	0.248	0.333	0.447	0.575	-	-
DX60C3	0.014	0.030	0.063	0.106	0.148	0.191	0.234	0.305	0.376
DX60C4	0.016	0.035	0.092	0.148	0.205	0.262	0.333	0.418	0.518
DX60D3	0.011	0.023	0.049	0.106	0.148	0.191	0.234	0.291	0.362
DX60D4	0.016	0.035	0.092	0.148	0.205	0.262	0.333	0.418	0.504
DX60E3	0.011	0.023	0.049	0.077	0.120	0.163	0.220	0.248	0.319
DX60E4	0.016	0.035	0.077	0.120	0.177	0.234	0.291	0.362	0.433
DX60F3	0.023	0.049	0.106	0.177	0.220	0.305	0.404	0.504	0.617
DX60F4	0.044	0.092	0.163	0.234	0.319	0.433	0.561	0.688	-

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com