



SAFE-T-SWITCH[®] SS2

#97087

Instructions inside. Instructions à l'intérieur. Instrucciones dentro.

► FEATURES & BENEFITS

- Prevents water damage from clogged drains
- Adjustable float – no cap removal
- Magnetic reed switch
- ¾" adapter included
- Easy service access
- Red or yellow wire connection

► CARACTERÍSTICAS Y BENEFICIOS

- Evita daños por agua causados por desagües obstruidos
- Flotador ajustable: no requiere quitar la tapa
- Interruptor magnético de láminas
- Adaptador de ¾" incluido
- Fácil acceso para mantenimiento
- Conexión de cable rojo o amarillo

► CARACTÉRISTIQUES ET AVANTAGES

- Prévient les dégâts d'eau causés par les canalisations bouchées
- Flotteur réglable – aucun retrait du bouchon
- Interrupteur magnétique à lames
- Adaptateur ¾" inclus
- Accès facile pour l'entretien
- Connexion par fil rouge ou jaune



RectorSeal[®]
2601 Spenwick Drive, Houston, TX 77055, 800-231-3345
RectorSeal.com

MADE IN THAILAND
HECHO EN TAILANDIA
FABRIQUE EN THAILANDE

©2026 RectorSeal.
All rights reserved.
R50109-260708



0 21449 97087 7

SAFE-T-SWITCH[®] SS2

SAFE-T-SWITCH[®] SS2

#97087

CONDENSATE
OVERFLOW SWITCH
INTERRUPTOR DE
DESBORDAMIENTO
DE CONDENSADO
INTERRUPTEUR
DE TROP-PLEIN
DE CONDENSATS

SAFE-T-SWITCH[®] SS2



5036240
Conforms to
UL STD 508
Certified to CSA
STD C22.2#14



ETL CLASSIFIED
5036240
Conforms to
UL STD 2043
Certified to
ULC STD S142

Instructions. Videos. *Warranty.
Instrucciones. Vídeos. *Garantía.
Instrucciones. Vídeos. *Garantía.

