# CA/CC/CE SERIES

►COPPER COIL
►UPFLOW / DOWNFLOW

**CA/CC/CE SERIES (HIGH EFFICIENCY):** DIMENSIONAL DATA (In.)

| COIL MODELS | Dry Coil Static Pressure Drop (in. w.c.) @ CFM | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 400 | 600 | 800 | 1000 | 1200 | 1400 | 1600 | 1800 | 2000 |
| C(A/C/E)24A2 | 0.084 | 0.128 | 0.215 | 0.325 | 0.442 | 0.581 | - | - | - |
| C(A/C/E)24A3 | 0.098 | 0.171 | 0.289 | 0.435 | 0.589 | - | - | - | - |
| C(A/C/E)24A4 | 0.098 | 0.208 | 0.340 | 0.508 | - | - | - | - | - |
| C(A/C/E)24B2 | 0.062 | 0.091 | 0.164 | 0.245 | 0.340 | 0.442 | 0.559 | - | - |
| C(A/C/E)24B3 | 0.091 | 0.149 | 0.252 | 0.369 | 0.508 | - | - | - | - |
| C(A/C/E)24B4 | 0.098 | 0.179 | 0.296 | 0.442 | - | - | - | - | - |
| C(A/C/E)24C2 | 0.047 | 0.098 | 0.128 | 0.193 | 0.267 | 0.354 | 0.442 | 0.545 | - |
| C(A/C/E)24C3 | 0.076 | 0.142 | 0.201 | 0.296 | 0.406 | 0.530 | - | - | - |
| C(A/C/E)24C4 | 0.106 | 0.186 | 0.267 | 0.398 | 0.537 | - | - | - | - |
| C(A/C/E)24D2 | 0.040 | 0.084 | 0.098 | 0.157 | 0.215 | 0.289 | 0.362 | 0.442 | 0.530 |
| C(A/C/E)24D3 | 0.062 | 0.120 | 0.157 | 0.237 | 0.332 | 0.435 | 0.545 | - | - |
| C(A/C/E)24D4 | 0.084 | 0.157 | 0.215 | 0.325 | 0.442 | 0.574 | - | - | - |
| C(A/C/E)30A2 | 0.047 | 0.084 | 0.142 | 0.215 | 0.303 | 0.391 | 0.493 | - | - |
| C(A/C/E)30A3 | 0.062 | 0.113 | 0.193 | 0.289 | 0.398 | 0.515 | - | - | - |
| C(A/C/E)30A4 | 0.076 | 0.157 | 0.259 | 0.384 | 0.530 | - | - | - | - |
| C(A/C/E)30B2 | 0.047 | 0.098 | 0.128 | 0.193 | 0.267 | 0.354 | 0.442 | 0.545 | - |
| C(A/C/E)30B3 | 0.062 | 0.113 | 0.171 | 0.259 | 0.362 | 0.471 | 0.589 | - | - |
| C(A/C/E)30B4 | 0.084 | 0.149 | 0.237 | 0.347 | 0.479 | - | - | - | - |
| C(A/C/E)30C2 | 0.040 | 0.084 | 0.098 | 0.157 | 0.215 | 0.289 | 0.362 | 0.442 | 0.530 |
| C(A/C/E)30C3 | 0.062 | 0.120 | 0.157 | 0.237 | 0.332 | 0.435 | 0.545 | - | - |
| C(A/C/E)30C4 | 0.084 | 0.157 | 0.215 | 0.325 | 0.442 | 0.574 | - | - | - |
| C(A/C/E)30D2 | 0.034 | 0.069 | 0.106 | 0.128 | 0.179 | 0.237 | 0.303 | 0.369 | 0.442 |
| C(A/C/E)30D3 | 0.054 | 0.098 | 0.157 | 0.201 | 0.274 | 0.362 | 0.449 | 0.552 | - |
| C(A/C/E)30D4 | 0.069 | 0.135 | 0.201 | 0.267 | 0.369 | 0.479 | - | - | - |
| C(A/C/E)30E3 | 0.062 | 0.113 | 0.171 | 0.208 | 0.289 | 0.384 | 0.479 | 0.589 | - |
| C(A/C/E)30E4 | 0.084 | 0.149 | 0.223 | 0.281 | 0.391 | 0.508 | - | - | - |
| C(A/C/E)36A2 | 0.040 | 0.076 | 0.113 | 0.171 | 0.237 | 0.310 | 0.391 | 0.486 | 0.581 |
| C(A/C/E)36A3 | 0.047 | 0.091 | 0.149 | 0.230 | 0.318 | 0.413 | 0.515 | - | - |
| C(A/C/E)36A4 | 0.062 | 0.120 | 0.208 | 0.303 | 0.420 | 0.552 | - | - | - |
| C(A/C/E)36B2 | 0.040 | 0.084 | 0.098 | 0.157 | 0.215 | 0.289 | 0.362 | 0.442 | 0.530 |
| C(A/C/E)36B3 | 0.047 | 0.098 | 0.142 | 0.208 | 0.289 | 0.384 | 0.479 | 0.589 | - |
| C(A/C/E)36B4 | 0.054 | 0.098 | 0.164 | 0.245 | 0.340 | 0.449 | 0.567 | - | - |
| C(A/C/E)36C2 | 0.034 | 0.069 | 0.106 | 0.128 | 0.179 | 0.237 | 0.303 | 0.369 | 0.442 |
| C(A/C/E)36C3 | 0.040 | 0.084 | 0.128 | 0.171 | 0.245 | 0.318 | 0.398 | 0.493 | 0.589 |
| C(A/C/E)36C4 | 0.054 | 0.106 | 0.164 | 0.237 | 0.325 | 0.428 | 0.537 | - | - |
| C(A/C/E)36D2 | 0.031 | 0.062 | 0.091 | 0.106 | 0.149 | 0.201 | 0.252 | 0.310 | 0.376 |
| C(A/C/E)36D3 | 0.047 | 0.091 | 0.135 | 0.164 | 0.230 | 0.303 | 0.384 | 0.471 | 0.567 |
| C(A/C/E)36D4 | 0.062 | 0.113 | 0.179 | 0.223 | 0.310 | 0.406 | 0.515 | - | - |
| C(A/C/E)36E2 | 0.047 | 0.098 | 0.128 | 0.193 | 0.267 | 0.354 | 0.442 | 0.545 | - |
| C(A/C/E)36E3 | 0.062 | 0.113 | 0.171 | 0.259 | 0.362 | 0.471 | 0.589 | - | - |
| C(A/C/E)36E4 | 0.084 | 0.149 | 0.237 | 0.347 | 0.479 | - | - | - | - |
| C(A/C/E)36F2 | 0.024 | 0.047 | 0.069 | 0.098 | 0.113 | 0.149 | 0.186 | 0.230 | 0.281 |
| C(A/C/E)36F3 | 0.034 | 0.069 | 0.106 | 0.149 | 0.171 | 0.223 | 0.289 | 0.354 | 0.420 |
| C(A/C/E)36F4 | 0.047 | 0.091 | 0.135 | 0.186 | 0.230 | 0.303 | 0.384 | 0.471 | 0.567 |
| C(A/C/E)42A2 | 0.031 | 0.062 | 0.091 | 0.135 | 0.193 | 0.252 | 0.318 | 0.391 | 0.471 |
| C(A/C/E)42A3 | 0.040 | 0.076 | 0.120 | 0.186 | 0.252 | 0.332 | 0.420 | 0.515 | - |
| C(A/C/E)42A4 | 0.040 | 0.076 | 0.142 | 0.215 | 0.296 | 0.384 | 0.486 | 0.596 | - |
| C(A/C/E)42B2 | 0.027 | 0.054 | 0.084 | 0.113 | 0.157 | 0.208 | 0.267 | 0.325 | 0.391 |

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

**Phone:** 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

## Continued... CA/CC/CE SERIES (HIGH EFFICIENCY): DIMENSIONAL DATA (In.)

| COIL MODELS | Dry Coil Static Pressure Drop (in. w.c.) @ CFM | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 400 | 600 | 800 | 1000 | 1200 | 1400 | 1600 | 1800 | 2000 |
| C(A/C/E)42B3 | 0.031 | 0.062 | 0.098 | 0.149 | 0.208 | 0.281 | 0.354 | 0.435 | 0.515 |
| C(A/C/E)42B4 | 0.047 | 0.084 | 0.135 | 0.208 | 0.281 | 0.376 | 0.471 | 0.574 | - |
| C(A/C/E)42C2 | 0.031 | 0.062 | 0.091 | 0.106 | 0.149 | 0.201 | 0.252 | 0.310 | 0.376 |
| C(A/C/E)42C3 | 0.034 | 0.069 | 0.113 | 0.142 | 0.201 | 0.267 | 0.340 | 0.420 | 0.501 |
| C(A/C/E)42C4 | 0.047 | 0.091 | 0.142 | 0.201 | 0.274 | 0.362 | 0.457 | 0.559 | - |
| C(A/C/E)42D2 | 0.024 | 0.047 | 0.076 | 0.091 | 0.128 | 0.171 | 0.215 | 0.267 | 0.325 |
| C(A/C/E)42D3 | 0.040 | 0.076 | 0.120 | 0.142 | 0.201 | 0.259 | 0.332 | 0.406 | 0.486 |
| C(A/C/E)42D4 | 0.040 | 0.084 | 0.128 | 0.171 | 0.237 | 0.310 | 0.391 | 0.479 | 0.574 |
| C(A/C/E)42E2 | 0.040 | 0.084 | 0.098 | 0.157 | 0.215 | 0.289 | 0.362 | 0.442 | 0.530 |
| C(A/C/E)42E3 | 0.047 | 0.098 | 0.142 | 0.208 | 0.289 | 0.384 | 0.479 | 0.589 | - |
| C(A/C/E)42E4 | 0.054 | 0.098 | 0.164 | 0.245 | 0.340 | 0.449 | 0.567 | - | - |
| C(A/C/E)42F2 | 0.024 | 0.047 | 0.069 | 0.098 | 0.113 | 0.149 | 0.186 | 0.230 | 0.281 |
| C(A/C/E)42F3 | 0.034 | 0.069 | 0.106 | 0.149 | 0.171 | 0.223 | 0.289 | 0.354 | 0.420 |
| C(A/C/E)42F4 | 0.040 | 0.076 | 0.113 | 0.157 | 0.201 | 0.267 | 0.340 | 0.420 | 0.501 |
| C(A/C/E)48A2 | 0.020 | 0.040 | 0.069 | 0.098 | 0.135 | 0.179 | 0.230 | 0.289 | 0.347 |
| C(A/C/E)48A3 | 0.031 | 0.062 | 0.098 | 0.149 | 0.208 | 0.281 | 0.354 | 0.435 | 0.515 |
| C(A/C/E)48A4 | 0.031 | 0.062 | 0.098 | 0.179 | 0.245 | 0.318 | 0.406 | 0.501 | 0.596 |
| C(A/C/E)48B2 | 0.024 | 0.047 | 0.076 | 0.091 | 0.135 | 0.179 | 0.223 | 0.274 | 0.332 |
| C(A/C/E)48B3 | 0.027 | 0.054 | 0.084 | 0.128 | 0.179 | 0.237 | 0.296 | 0.369 | 0.442 |
| C(A/C/E)48B4 | 0.040 | 0.076 | 0.113 | 0.171 | 0.237 | 0.318 | 0.398 | 0.486 | 0.589 |
| C(A/C/E)48C2 | 0.024 | 0.047 | 0.076 | 0.091 | 0.128 | 0.171 | 0.215 | 0.267 | 0.325 |
| C(A/C/E)48C3 | 0.031 | 0.062 | 0.098 | 0.120 | 0.171 | 0.230 | 0.289 | 0.362 | 0.435 |
| C(A/C/E)48C4 | 0.031 | 0.062 | 0.098 | 0.142 | 0.208 | 0.274 | 0.340 | 0.420 | 0.508 |
| C(A/C/E)48D2 | 0.024 | 0.047 | 0.069 | 0.098 | 0.113 | 0.149 | 0.186 | 0.230 | 0.281 |
| C(A/C/E)48D3 | 0.027 | 0.054 | 0.084 | 0.120 | 0.149 | 0.201 | 0.252 | 0.310 | 0.376 |
| C(A/C/E)48D4 | 0.040 | 0.076 | 0.113 | 0.157 | 0.201 | 0.267 | 0.340 | 0.420 | 0.501 |
| C(A/C/E)48F3 | 0.034 | 0.069 | 0.106 | 0.135 | 0.186 | 0.245 | 0.310 | 0.384 | 0.457 |
| C(A/C/E)48F4 | 0.040 | 0.076 | 0.113 | 0.157 | 0.223 | 0.289 | 0.369 | 0.449 | 0.537 |
| C(A/C/E)48G3 | 0.031 | 0.062 | 0.098 | 0.135 | 0.157 | 0.215 | 0.267 | 0.332 | 0.398 |
| C(A/C/E)48G4 | 0.040 | 0.084 | 0.128 | 0.171 | 0.215 | 0.289 | 0.362 | 0.442 | 0.530 |
| C(A/C/E)48H2 | 0.027 | 0.054 | 0.084 | 0.113 | 0.157 | 0.208 | 0.267 | 0.325 | 0.391 |
| C(A/C/E)48H3 | 0.040 | 0.084 | 0.128 | 0.171 | 0.245 | 0.318 | 0.398 | 0.493 | 0.589 |
| C(A/C/E)48H4 | 0.047 | 0.084 | 0.135 | 0.208 | 0.281 | 0.376 | 0.471 | 0.574 | - |
| C(A/C/E)60A2 | 0.012 | 0.024 | 0.047 | 0.069 | 0.098 | 0.128 | 0.164 | 0.208 | 0.252 |
| C(A/C/E)60A3 | 0.024 | 0.047 | 0.076 | 0.106 | 0.149 | 0.201 | 0.252 | 0.318 | 0.376 |
| C(A/C/E)60A4 | 0.024 | 0.047 | 0.076 | 0.106 | 0.179 | 0.230 | 0.296 | 0.362 | 0.435 |
| C(A/C/E)60B2 | 0.014 | 0.027 | 0.054 | 0.084 | 0.098 | 0.128 | 0.164 | 0.208 | 0.245 |
| C(A/C/E)60B3 | 0.020 | 0.040 | 0.069 | 0.091 | 0.128 | 0.171 | 0.223 | 0.274 | 0.325 |
| C(A/C/E)60B4 | 0.040 | 0.076 | 0.113 | 0.157 | 0.201 | 0.267 | 0.340 | 0.420 | 0.501 |
| C(A/C/E)60C2 | 0.014 | 0.027 | 0.054 | 0.076 | 0.091 | 0.120 | 0.157 | 0.193 | 0.230 |
| C(A/C/E)60C3 | 0.020 | 0.040 | 0.062 | 0.091 | 0.120 | 0.164 | 0.208 | 0.252 | 0.310 |
| C(A/C/E)60C4 | 0.034 | 0.069 | 0.106 | 0.149 | 0.193 | 0.252 | 0.318 | 0.391 | 0.471 |
| C(A/C/E)60D2 | 0.012 | 0.024 | 0.047 | 0.069 | 0.091 | 0.106 | 0.135 | 0.164 | 0.201 |
| C(A/C/E)60D3 | 0.024 | 0.047 | 0.069 | 0.098 | 0.135 | 0.157 | 0.208 | 0.252 | 0.303 |
| C(A/C/E)60D4 | 0.024 | 0.047 | 0.076 | 0.106 | 0.135 | 0.186 | 0.245 | 0.296 | 0.362 |
| C(A/C/E)60E2 | 0.012 | 0.024 | 0.047 | 0.069 | 0.091 | 0.098 | 0.120 | 0.157 | 0.186 |
| C(A/C/E)60E3 | 0.020 | 0.040 | 0.062 | 0.084 | 0.113 | 0.135 | 0.171 | 0.208 | 0.252 |
| C(A/C/E)60E4 | 0.024 | 0.047 | 0.084 | 0.113 | 0.149 | 0.179 | 0.230 | 0.281 | 0.340 |
| C(A/C/E)60F3 | 0.027 | 0.054 | 0.084 | 0.113 | 0.164 | 0.215 | 0.274 | 0.340 | 0.406 |
| C(A/C/E)60F4 | 0.027 | 0.054 | 0.091 | 0.120 | 0.193 | 0.252 | 0.318 | 0.391 | 0.471 |
| C(A/C/E)60G3 | 0.020 | 0.040 | 0.069 | 0.098 | 0.128 | 0.142 | 0.179 | 0.223 | 0.267 |
| C(A/C/E)60G4 | 0.027 | 0.054 | 0.091 | 0.128 | 0.164 | 0.193 | 0.245 | 0.303 | 0.362 |

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

**Phone:** 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

# CA/CC/CE SERIES

►COPPER COIL
►UPFLOW / DOWNFLOW

**CA/CC/CE SERIES (HIGH EFFICIENCY):** DIMENSIONAL DATA (In.)

| COIL MODELS | Wet Coil Static Pressure Drop (in. w.c.) @ CFM | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 400 | 600 | 800 | 1000 | 1200 | 1400 | 1600 | 1800 | 2000 |
| C(A/C/E)24A2 | 0.113 | 0.181 | 0.318 | 0.489 | 0.671 | 0.887 | - | - | - |
| C(A/C/E)24A3 | 0.136 | 0.250 | 0.432 | 0.659 | 0.898 | - | - | - | - |
| C(A/C/E)24A4 | 0.136 | 0.307 | 0.511 | 0.773 | - | - | - | - | - |
| C(A/C/E)24B2 | 0.079 | 0.125 | 0.238 | 0.363 | 0.511 | 0.671 | 0.853 | - | - |
| C(A/C/E)24B3 | 0.125 | 0.216 | 0.375 | 0.557 | 0.773 | - | - | - | - |
| C(A/C/E)24B4 | 0.136 | 0.261 | 0.443 | 0.671 | - | - | - | - | - |
| C(A/C/E)24C2 | 0.057 | 0.130 | 0.171 | 0.264 | 0.368 | 0.493 | 0.617 | 0.762 | - |
| C(A/C/E)24C3 | 0.098 | 0.192 | 0.275 | 0.410 | 0.565 | 0.741 | - | - | - |
| C(A/C/E)24C4 | 0.140 | 0.254 | 0.368 | 0.555 | 0.752 | - | - | - | - |
| C(A/C/E)24D2 | 0.047 | 0.109 | 0.130 | 0.212 | 0.295 | 0.399 | 0.503 | 0.617 | 0.741 |
| C(A/C/E)24D3 | 0.078 | 0.161 | 0.212 | 0.327 | 0.461 | 0.607 | 0.762 | - | - |
| C(A/C/E)24D4 | 0.109 | 0.212 | 0.295 | 0.451 | 0.617 | 0.804 | - | - | - |
| C(A/C/E)30A2 | 0.056 | 0.113 | 0.204 | 0.318 | 0.454 | 0.591 | 0.750 | - | - |
| C(A/C/E)30A3 | 0.079 | 0.159 | 0.284 | 0.432 | 0.602 | 0.784 | - | - | - |
| C(A/C/E)30A4 | 0.102 | 0.227 | 0.386 | 0.580 | 0.807 | - | - | - | - |
| C(A/C/E)30B2 | 0.057 | 0.130 | 0.171 | 0.264 | 0.368 | 0.493 | 0.617 | 0.762 | - |
| C(A/C/E)30B3 | 0.078 | 0.150 | 0.233 | 0.358 | 0.503 | 0.658 | 0.824 | - | - |
| C(A/C/E)30B4 | 0.109 | 0.202 | 0.327 | 0.482 | 0.669 | - | - | - | - |
| C(A/C/E)30C2 | 0.047 | 0.109 | 0.130 | 0.212 | 0.295 | 0.399 | 0.503 | 0.617 | 0.741 |
| C(A/C/E)30C3 | 0.078 | 0.161 | 0.212 | 0.327 | 0.461 | 0.607 | 0.762 | - | - |
| C(A/C/E)30C4 | 0.109 | 0.212 | 0.295 | 0.451 | 0.617 | 0.804 | - | - | - |
| C(A/C/E)30D2 | 0.039 | 0.088 | 0.140 | 0.171 | 0.244 | 0.327 | 0.420 | 0.513 | 0.617 |
| C(A/C/E)30D3 | 0.067 | 0.130 | 0.212 | 0.275 | 0.378 | 0.503 | 0.627 | 0.773 | - |
| C(A/C/E)30D4 | 0.088 | 0.181 | 0.275 | 0.368 | 0.513 | 0.669 | - | - | - |
| C(A/C/E)30E3 | 0.078 | 0.150 | 0.233 | 0.285 | 0.399 | 0.534 | 0.669 | 0.824 | - |
| C(A/C/E)30E4 | 0.109 | 0.202 | 0.306 | 0.389 | 0.544 | 0.710 | - | - | - |
| C(A/C/E)36A2 | 0.047 | 0.098 | 0.150 | 0.233 | 0.327 | 0.430 | 0.544 | 0.679 | 0.814 |
| C(A/C/E)36A3 | 0.057 | 0.119 | 0.202 | 0.316 | 0.441 | 0.576 | 0.721 | - | - |
| C(A/C/E)36A4 | 0.078 | 0.161 | 0.285 | 0.420 | 0.586 | 0.773 | - | - | - |
| C(A/C/E)36B2 | 0.047 | 0.109 | 0.130 | 0.212 | 0.295 | 0.399 | 0.503 | 0.617 | 0.741 |
| C(A/C/E)36B3 | 0.057 | 0.130 | 0.192 | 0.285 | 0.399 | 0.534 | 0.669 | 0.824 | - |
| C(A/C/E)36B4 | 0.067 | 0.130 | 0.223 | 0.337 | 0.472 | 0.627 | 0.793 | - | - |
| C(A/C/E)36C2 | 0.039 | 0.088 | 0.140 | 0.171 | 0.244 | 0.327 | 0.420 | 0.513 | 0.617 |
| C(A/C/E)36C3 | 0.047 | 0.109 | 0.171 | 0.233 | 0.337 | 0.441 | 0.555 | 0.690 | 0.824 |
| C(A/C/E)36C4 | 0.067 | 0.140 | 0.223 | 0.327 | 0.451 | 0.596 | 0.752 | - | - |
| C(A/C/E)36D2 | 0.034 | 0.078 | 0.119 | 0.140 | 0.202 | 0.275 | 0.347 | 0.430 | 0.524 |
| C(A/C/E)36D3 | 0.057 | 0.119 | 0.181 | 0.223 | 0.316 | 0.420 | 0.534 | 0.658 | 0.793 |
| C(A/C/E)36D4 | 0.078 | 0.150 | 0.244 | 0.306 | 0.430 | 0.565 | 0.721 | - | - |
| C(A/C/E)36E2 | 0.057 | 0.130 | 0.171 | 0.264 | 0.368 | 0.493 | 0.617 | 0.762 | 0.907 |
| C(A/C/E)36E3 | 0.078 | 0.150 | 0.233 | 0.358 | 0.503 | 0.658 | 0.824 | - | - |
| C(A/C/E)36E4 | 0.109 | 0.202 | 0.327 | 0.482 | 0.669 | - | - | - | - |
| C(A/C/E)36F2 | 0.024 | 0.057 | 0.088 | 0.130 | 0.150 | 0.202 | 0.254 | 0.316 | 0.389 |
| C(A/C/E)36F3 | 0.039 | 0.088 | 0.140 | 0.202 | 0.233 | 0.306 | 0.399 | 0.493 | 0.586 |
| C(A/C/E)36F4 | 0.057 | 0.119 | 0.181 | 0.254 | 0.316 | 0.420 | 0.534 | 0.658 | 0.793 |
| C(A/C/E)42A2 | 0.034 | 0.078 | 0.119 | 0.181 | 0.264 | 0.347 | 0.441 | 0.544 | 0.658 |
| C(A/C/E)42A3 | 0.047 | 0.098 | 0.161 | 0.254 | 0.347 | 0.461 | 0.586 | 0.721 | 0.876 |
| C(A/C/E)42A4 | 0.047 | 0.098 | 0.192 | 0.295 | 0.410 | 0.534 | 0.679 | 0.835 | - |
| C(A/C/E)42B2 | 0.029 | 0.067 | 0.109 | 0.150 | 0.212 | 0.285 | 0.368 | 0.451 | 0.544 |

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

**Phone:** 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

## Continued... CA/CC/CE SERIES (HIGH EFFICIENCY): DIMENSIONAL DATA (In.)

| COIL MODELS | Wet Coil Static Pressure Drop (in. w.c.) @ CFM | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 400 | 600 | 800 | 1000 | 1200 | 1400 | 1600 | 1800 | 2000 |
| C(A/C/E)42B3 | 0.034 | 0.078 | 0.130 | 0.202 | 0.285 | 0.389 | 0.493 | 0.607 | 0.721 |
| C(A/C/E)42B4 | 0.057 | 0.109 | 0.181 | 0.285 | 0.389 | 0.524 | 0.658 | 0.804 | - |
| C(A/C/E)42C2 | 0.034 | 0.078 | 0.119 | 0.140 | 0.202 | 0.275 | 0.347 | 0.430 | 0.524 |
| C(A/C/E)42C3 | 0.039 | 0.088 | 0.150 | 0.192 | 0.275 | 0.368 | 0.472 | 0.586 | 0.700 |
| C(A/C/E)42C4 | 0.057 | 0.119 | 0.192 | 0.275 | 0.378 | 0.503 | 0.638 | 0.783 | - |
| C(A/C/E)42D2 | 0.024 | 0.049 | 0.085 | 0.103 | 0.149 | 0.203 | 0.258 | 0.321 | 0.394 |
| C(A/C/E)42D3 | 0.040 | 0.085 | 0.140 | 0.167 | 0.239 | 0.312 | 0.403 | 0.493 | 0.593 |
| C(A/C/E)42D4 | 0.040 | 0.094 | 0.149 | 0.203 | 0.285 | 0.375 | 0.475 | 0.584 | 0.702 |
| C(A/C/E)42E2 | 0.047 | 0.109 | 0.130 | 0.212 | 0.295 | 0.399 | 0.503 | 0.617 | 0.741 |
| C(A/C/E)42E3 | 0.057 | 0.130 | 0.192 | 0.285 | 0.399 | 0.534 | 0.669 | 0.824 | - |
| C(A/C/E)42E4 | 0.067 | 0.130 | 0.223 | 0.337 | 0.472 | 0.627 | 0.793 | 0.970 | - |
| C(A/C/E)42F2 | 0.024 | 0.049 | 0.076 | 0.112 | 0.130 | 0.176 | 0.221 | 0.276 | 0.339 |
| C(A/C/E)42F3 | 0.034 | 0.076 | 0.121 | 0.176 | 0.203 | 0.267 | 0.348 | 0.430 | 0.512 |
| C(A/C/E)42F4 | 0.040 | 0.085 | 0.130 | 0.185 | 0.239 | 0.321 | 0.412 | 0.512 | 0.611 |
| C(A/C/E)48A2 | 0.020 | 0.047 | 0.088 | 0.130 | 0.181 | 0.244 | 0.316 | 0.399 | 0.482 |
| C(A/C/E)48A3 | 0.034 | 0.078 | 0.130 | 0.202 | 0.285 | 0.389 | 0.493 | 0.607 | 0.721 |
| C(A/C/E)48A4 | 0.034 | 0.078 | 0.130 | 0.244 | 0.337 | 0.441 | 0.565 | 0.700 | 0.835 |
| C(A/C/E)48B2 | 0.024 | 0.057 | 0.098 | 0.119 | 0.181 | 0.244 | 0.306 | 0.378 | 0.461 |
| C(A/C/E)48B3 | 0.029 | 0.067 | 0.109 | 0.171 | 0.244 | 0.327 | 0.410 | 0.513 | 0.617 |
| C(A/C/E)48B4 | 0.047 | 0.098 | 0.150 | 0.233 | 0.327 | 0.441 | 0.555 | 0.679 | 0.824 |
| C(A/C/E)48C2 | 0.024 | 0.049 | 0.085 | 0.103 | 0.149 | 0.203 | 0.258 | 0.321 | 0.394 |
| C(A/C/E)48C3 | 0.031 | 0.067 | 0.112 | 0.140 | 0.203 | 0.276 | 0.348 | 0.439 | 0.530 |
| C(A/C/E)48C4 | 0.031 | 0.067 | 0.112 | 0.167 | 0.248 | 0.330 | 0.412 | 0.512 | 0.620 |
| C(A/C/E)48D2 | 0.024 | 0.049 | 0.076 | 0.112 | 0.130 | 0.176 | 0.221 | 0.276 | 0.339 |
| C(A/C/E)48D3 | 0.027 | 0.058 | 0.094 | 0.140 | 0.176 | 0.239 | 0.303 | 0.375 | 0.457 |
| C(A/C/E)48D4 | 0.040 | 0.085 | 0.130 | 0.185 | 0.239 | 0.321 | 0.412 | 0.512 | 0.611 |
| C(A/C/E)48F3 | 0.034 | 0.076 | 0.121 | 0.158 | 0.221 | 0.294 | 0.375 | 0.466 | 0.557 |
| C(A/C/E)48F4 | 0.040 | 0.085 | 0.130 | 0.185 | 0.267 | 0.348 | 0.448 | 0.548 | 0.657 |
| C(A/C/E)48G3 | 0.031 | 0.067 | 0.112 | 0.158 | 0.185 | 0.258 | 0.321 | 0.403 | 0.484 |
| C(A/C/E)48G4 | 0.040 | 0.094 | 0.149 | 0.203 | 0.258 | 0.348 | 0.439 | 0.539 | 0.648 |
| C(A/C/E)48H2 | 0.029 | 0.067 | 0.109 | 0.150 | 0.212 | 0.285 | 0.368 | 0.451 | 0.544 |
| C(A/C/E)48H3 | 0.047 | 0.109 | 0.171 | 0.233 | 0.337 | 0.441 | 0.555 | 0.690 | 0.824 |
| C(A/C/E)48H4 | 0.057 | 0.109 | 0.181 | 0.285 | 0.389 | 0.524 | 0.658 | 0.804 | - |
| C(A/C/E)60A2 | 0.012 | 0.024 | 0.049 | 0.076 | 0.112 | 0.149 | 0.194 | 0.248 | 0.303 |
| C(A/C/E)60A3 | 0.024 | 0.049 | 0.085 | 0.121 | 0.176 | 0.239 | 0.303 | 0.385 | 0.457 |
| C(A/C/E)60A4 | 0.024 | 0.049 | 0.085 | 0.121 | 0.212 | 0.276 | 0.357 | 0.439 | 0.530 |
| C(A/C/E)60B2 | 0.014 | 0.027 | 0.058 | 0.094 | 0.112 | 0.149 | 0.194 | 0.248 | 0.294 |
| C(A/C/E)60B3 | 0.020 | 0.040 | 0.076 | 0.103 | 0.149 | 0.203 | 0.267 | 0.330 | 0.394 |
| C(A/C/E)60B4 | 0.040 | 0.085 | 0.130 | 0.185 | 0.239 | 0.321 | 0.412 | 0.512 | 0.611 |
| C(A/C/E)60C2 | 0.014 | 0.027 | 0.058 | 0.085 | 0.103 | 0.140 | 0.185 | 0.230 | 0.276 |
| C(A/C/E)60C3 | 0.020 | 0.040 | 0.067 | 0.103 | 0.140 | 0.194 | 0.248 | 0.303 | 0.375 |
| C(A/C/E)60C4 | 0.034 | 0.076 | 0.121 | 0.176 | 0.230 | 0.303 | 0.385 | 0.475 | 0.575 |
| C(A/C/E)60D2 | 0.012 | 0.024 | 0.049 | 0.076 | 0.103 | 0.121 | 0.158 | 0.194 | 0.239 |
| C(A/C/E)60D3 | 0.024 | 0.049 | 0.076 | 0.112 | 0.158 | 0.185 | 0.248 | 0.303 | 0.366 |
| C(A/C/E)60D4 | 0.024 | 0.049 | 0.085 | 0.121 | 0.158 | 0.221 | 0.294 | 0.357 | 0.439 |
| C(A/C/E)60E2 | 0.012 | 0.024 | 0.049 | 0.076 | 0.103 | 0.112 | 0.140 | 0.185 | 0.221 |
| C(A/C/E)60E3 | 0.020 | 0.040 | 0.067 | 0.094 | 0.130 | 0.158 | 0.203 | 0.248 | 0.303 |
| C(A/C/E)60E4 | 0.024 | 0.049 | 0.094 | 0.130 | 0.176 | 0.212 | 0.276 | 0.339 | 0.412 |
| C(A/C/E)60F3 | 0.027 | 0.058 | 0.094 | 0.130 | 0.194 | 0.258 | 0.330 | 0.412 | 0.493 |
| C(A/C/E)60F4 | 0.027 | 0.058 | 0.103 | 0.140 | 0.230 | 0.303 | 0.385 | 0.475 | 0.575 |
| C(A/C/E)60G3 | 0.020 | 0.040 | 0.076 | 0.112 | 0.149 | 0.167 | 0.212 | 0.267 | 0.321 |
| C(A/C/E)60G4 | 0.027 | 0.058 | 0.103 | 0.149 | 0.194 | 0.230 | 0.294 | 0.366 | 0.439 |

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

**Phone:** 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com