CX SERIES

►COPPER COIL
►DEDICATED HORIZONTAL

CX SERIES: DIMENSIONAL DATA (In.)									
COIL MODELS	Dry Coil Static Pressure Drop (in. w.c.) @ CFM								
	400	600	800	1000	1200	1400	1600	1800	2000
CX24A3	0.130	0.252	0.447	-	-	-	-	-	-
CX24A4	0.179	0.361	0.552	-	-	-	-	-	-
CX24B3	0.093	0.179	0.337	-	-	-	-	-	-
CX24B4	0.130	0.264	0.459	-	-	-	-	-	-
CX30A3	0.093	0.179	0.337	0.520	-	-	-	-	-
CX30A4	0.130	0.264	0.459	-	-	-	-	-	-
CX36A3	0.093	0.179	0.337	0.520	-	-	-	-	-
CX36A4	0.130	0.264	0.459	-	-	-	-	-	-
CX36C3	0.069	0.154	0.252	0.398	0.568	-	-	-	-
CX36C4	0.106	0.215	0.361	0.544	-	-	-	-	-
CX36B3	0.045	0.130	0.203	0.313	0.447	-	-	-	-
CX36B4	0.081	0.179	0.288	0.434	-	-	-	-	-
CX24E2	0.028	0.057	0.106	0.154	0.227	0.313	-	-	-
CX24E3	0.033	0.106	0.179	0.252	0.374	0.495	-	-	-
CX24E4	0.057	0.142	0.240	0.361	0.508	-	-	-	-
CX48A3	0.033	0.106	0.179	0.252	0.374	0.495	-	-	-
CX48A4	0.057	0.142	0.240	0.361	0.508	-	-	-	-
CX30E3	0.033	0.093	0.167	0.227	0.337	0.447	-	-	-
CX30E4	0.057	0.130	0.227	0.325	0.459	-	-	-	-
CX36F3	0.033	0.093	0.167	0.227	0.337	0.447	-	-	-
CX36F4	0.057	0.130	0.227	0.325	0.459	-	-	-	-
CX48B3	0.041	0.081	0.142	0.203	0.288	0.398	0.508	-	-
CX48B4	0.045	0.118	0.203	0.288	0.410	0.544	-	-	-
CX36E3	0.035	0.069	0.130	0.179	0.264	0.361	0.471	-	-
CX36E4	0.045	0.106	0.179	0.252	0.374	0.495	-	-	-
CX48C3	0.035	0.069	0.130	0.179	0.264	0.361	0.471	-	-
CX48C4	0.045	0.106	0.179	0.252	0.374	0.495	-	-	-
CX42C3	0.028	0.057	0.118	0.179	0.240	0.325	0.422	0.520	-
CX42C4	0.033	0.093	0.167	0.240	0.337	0.447	0.568	-	-
CX60A3	0.028	0.057	0.118	0.179	0.240	0.325	0.422	0.520	-
CX60A4	0.033	0.093	0.167	0.240	0.337	0.447	0.568	-	-
CX42D3	0.028	0.057	0.106	0.167	0.215	0.288	0.386	0.471	-
CX42D4	0.041	0.081	0.154	0.227	0.301	0.410	0.520	-	-
CX36D3	0.022	0.045	0.106	0.154	0.203	0.276	0.361	0.447	0.544
CX36D4	0.041	0.081	0.142	0.215	0.288	0.386	0.495	-	-
CX48D3	0.022	0.045	0.106	0.154	0.203	0.276	0.361	0.447	0.544
CX48D4	0.041	0.081	0.142	0.215	0.288	0.386	0.495	-	-
CX60B3	0.022	0.045	0.106	0.154	0.203	0.276	0.361	0.447	0.544
CX60B4	0.041	0.081	0.142	0.215	0.288	0.386	0.495	-	-
CX60F3	0.022	0.045	0.093	0.154	0.191	0.264	0.349	0.434	0.532
CX60F4	0.041	0.081	0.142	0.203	0.276	0.374	0.483	0.593	-
CX60C3	0.014	0.028	0.057	0.093	0.130	0.167	0.203	0.264	0.325
CX60C4	0.016	0.033	0.081	0.130	0.179	0.227	0.288	0.361	0.447
CX60D3	0.011	0.022	0.045	0.081	0.130	0.167	0.203	0.252	0.313
CX60D4	0.016	0.033	0.081	0.130	0.179	0.227	0.288	0.361	0.434
CX60E3	0.011	0.022	0.045	0.069	0.106	0.142	0.186	0.215	0.264
CX60E4	0.016	0.033	0.069	0.106	0.154	0.203	0.252	0.301	0.374

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

CX SERIES

►COPPER COIL
►DEDICATED HORIZONTAL

CX SERIES: DIMENSIONAL DATA (In.)									
COIL MODELS	Wet Coil Static Pressure Drop (in. w.c.) @ CFM								
	400	600	800	1000	1200	1400	1600	1800	2000
CX24A3	0.153	0.299	0.532	-	-	-	-	-	-
CX24A4	0.211	0.430	-	-	-	-	-	-	-
CX24B3	0.109	0.211	0.401	-	-	-	-	-	-
CX24B4	0.153	0.313	0.547	-	-	-	-	-	-
CX30A3	0.109	0.211	0.401	0.620	-	-	-	-	-
CX30A4	0.153	0.313	0.547	-	-	-	-	-	-
CX36A3	0.109	0.211	0.401	0.620	-	-	-	-	-
CX36A4	0.153	0.313	0.547	-	-	-	-	-	-
CX36C3	0.082	0.188	0.309	0.491	0.703	-	-	-	-
CX36C4	0.128	0.264	0.446	0.673	-	-	-	-	-
CX36B3	0.052	0.158	0.249	0.385	0.552	-	-	-	-
CX36B4	0.098	0.219	0.355	0.536	-	-	-	-	-
CX24E2	0.032	0.067	0.128	0.188	0.279	0.385	-	-	-
CX24E3	0.037	0.128	0.219	0.309	0.461	0.612	-	-	-
CX24E4	0.067	0.173	0.294	0.446	0.627	-	-	-	-
CX48A3	0.037	0.128	0.219	0.309	0.461	0.612	-	-	-
CX48A4	0.067	0.173	0.294	0.446	0.627	-	-	-	-
CX30E3	0.037	0.113	0.203	0.279	0.415	0.552	-	-	-
CX30E4	0.067	0.158	0.279	0.400	0.567	-	-	-	-
CX36F3	0.037	0.113	0.203	0.279	0.415	0.552	-	-	-
CX36F4	0.067	0.158	0.279	0.400	0.567	-	-	-	-
CX48B3	0.047	0.098	0.173	0.249	0.355	0.491	0.627	-	-
CX48B4	0.052	0.143	0.249	0.355	0.506	0.673	-	-	-
CX36E3	0.039	0.082	0.158	0.219	0.325	0.446	0.582	-	-
CX36E4	0.052	0.128	0.219	0.309	0.461	0.612	-	-	-
CX48C3	0.039	0.082	0.158	0.219	0.325	0.446	0.582	-	-
CX48C4	0.052	0.128	0.219	0.309	0.461	0.612	-	-	-
CX42C3	0.032	0.067	0.143	0.219	0.294	0.400	0.521	0.642	-
CX42C4	0.037	0.113	0.203	0.294	0.415	0.552	0.703	-	-
CX60A3	0.032	0.067	0.143	0.219	0.294	0.400	0.521	0.642	-
CX60A4	0.037	0.113	0.203	0.294	0.415	0.552	0.703	-	-
CX42D3	0.032	0.067	0.128	0.203	0.264	0.355	0.476	0.582	-
CX42D4	0.047	0.098	0.188	0.279	0.370	0.506	0.642	-	-
CX36D3	0.023	0.049	0.120	0.177	0.234	0.319	0.418	0.518	0.632
CX36D4	0.044	0.092	0.163	0.248	0.333	0.447	0.575	-	-
CX48D3	0.023	0.049	0.120	0.177	0.234	0.319	0.418	0.518	0.632
CX48D4	0.044	0.092	0.163	0.248	0.333	0.447	0.575	-	-
CX60B3	0.023	0.049	0.120	0.177	0.234	0.319	0.418	0.518	0.632
CX60B4	0.044	0.092	0.163	0.248	0.333	0.447	0.575	-	-
CX60F3	0.023	0.049	0.106	0.177	0.220	0.305	0.404	0.504	0.617
CX60F4	0.044	0.092	0.163	0.234	0.319	0.433	0.561	0.688	-
CX60C3	0.014	0.030	0.063	0.106	0.148	0.191	0.234	0.305	0.376
CX60C4	0.016	0.035	0.092	0.148	0.205	0.262	0.333	0.418	0.518
CX60D3	0.011	0.023	0.049	0.092	0.148	0.191	0.234	0.291	0.362
CX60D4	0.016	0.035	0.092	0.148	0.205	0.262	0.333	0.418	0.504
CX60E3	0.011	0.023	0.049	0.077	0.120	0.163	0.214	0.248	0.305
CX60E4	0.016	0.035	0.077	0.120	0.177	0.234	0.291	0.347	0.433

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com