# CM SERIES

- UNCASED COPPER
- FOR MANUFACTURED HOMES
- UPFLOW / DOWNFLOW

| CM SERIES: DIMENSIONAL DATA (In.) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| COIL MODELS | Dry Coil Static Pressure Drop (in. w.c.) @ CFM | | | | | | | | |
| | 400 | 600 | 800 | 1000 | 1200 | 1400 | 1600 | 1800 | 2000 |
| CM24A2 | 0.084 | 0.128 | 0.215 | 0.325 | 0.442 | 0.581 | - | - | - |
| CM24A3 | 0.098 | 0.171 | 0.289 | 0.435 | 0.589 | - | - | - | - |
| CM24B2 | 0.062 | 0.091 | 0.164 | 0.245 | 0.340 | 0.442 | 0.559 | - | - |
| CM24B3 | 0.091 | 0.149 | 0.252 | 0.369 | 0.508 | - | - | - | - |
| CM24C2 | 0.047 | 0.098 | 0.128 | 0.193 | 0.267 | 0.354 | 0.442 | 0.545 | - |
| CM24C3 | 0.076 | 0.142 | 0.201 | 0.296 | 0.406 | 0.530 | - | - | - |
| CM24D2 | 0.040 | 0.084 | 0.098 | 0.157 | 0.215 | 0.289 | 0.362 | 0.442 | 0.530 |
| CM24D3 | 0.062 | 0.120 | 0.157 | 0.237 | 0.332 | 0.435 | 0.545 | - | - |
| CM30A2 | 0.047 | 0.084 | 0.142 | 0.215 | 0.303 | 0.391 | 0.493 | - | - |
| CM30A3 | 0.062 | 0.113 | 0.193 | 0.289 | 0.398 | 0.515 | - | - | - |
| CM30B2 | 0.047 | 0.098 | 0.128 | 0.193 | 0.267 | 0.354 | 0.442 | 0.545 | - |
| CM30B3 | 0.062 | 0.113 | 0.171 | 0.259 | 0.362 | 0.471 | 0.589 | - | - |
| CM30C2 | 0.040 | 0.084 | 0.098 | 0.157 | 0.215 | 0.289 | 0.362 | 0.442 | 0.530 |
| CM30C3 | 0.062 | 0.120 | 0.157 | 0.237 | 0.332 | 0.435 | 0.545 | - | - |
| CM36A2 | 0.040 | 0.076 | 0.113 | 0.171 | 0.237 | 0.310 | 0.391 | 0.486 | 0.581 |
| CM36A3 | 0.047 | 0.091 | 0.149 | 0.230 | 0.318 | 0.413 | 0.515 | - | - |
| CM36A4 | 0.062 | 0.120 | 0.208 | 0.303 | 0.420 | 0.552 | - | - | - |
| CM36B2 | 0.040 | 0.084 | 0.098 | 0.157 | 0.215 | 0.289 | 0.362 | 0.442 | 0.530 |
| CM36B3 | 0.047 | 0.098 | 0.142 | 0.208 | 0.289 | 0.384 | 0.479 | 0.589 | - |
| CM36B4 | 0.054 | 0.098 | 0.164 | 0.245 | 0.340 | 0.449 | 0.567 | - | - |
| CM36C3 | 0.040 | 0.084 | 0.128 | 0.171 | 0.245 | 0.318 | 0.398 | 0.493 | 0.589 |
| CM36E3 | 0.062 | 0.113 | 0.171 | 0.259 | 0.362 | 0.471 | 0.589 | - | - |
| CM36E4 | 0.084 | 0.149 | 0.237 | 0.347 | 0.479 | - | - | - | - |
| CM42A2 | 0.031 | 0.062 | 0.091 | 0.135 | 0.193 | 0.252 | 0.318 | 0.391 | 0.471 |
| CM42A3 | 0.040 | 0.076 | 0.120 | 0.186 | 0.252 | 0.332 | 0.420 | 0.515 | - |
| CM42A4 | 0.040 | 0.076 | 0.142 | 0.215 | 0.296 | 0.384 | 0.486 | 0.596 | - |
| CM48A3 | 0.031 | 0.062 | 0.098 | 0.149 | 0.208 | 0.281 | 0.354 | 0.435 | 0.515 |
| CM48A4 | 0.031 | 0.062 | 0.098 | 0.179 | 0.245 | 0.318 | 0.406 | 0.501 | 0.596 |
| CM48B3 | 0.027 | 0.054 | 0.084 | 0.128 | 0.179 | 0.237 | 0.296 | 0.369 | 0.442 |
| CM48B4 | 0.040 | 0.076 | 0.113 | 0.171 | 0.237 | 0.318 | 0.398 | 0.486 | 0.589 |
| CM48C3 | 0.031 | 0.062 | 0.098 | 0.120 | 0.171 | 0.230 | 0.289 | 0.362 | 0.435 |
| CM48C4 | 0.031 | 0.062 | 0.098 | 0.142 | 0.208 | 0.274 | 0.340 | 0.420 | 0.508 |
| CM48D3 | 0.027 | 0.054 | 0.084 | 0.120 | 0.149 | 0.201 | 0.252 | 0.310 | 0.376 |
| CM48D4 | 0.040 | 0.076 | 0.113 | 0.157 | 0.201 | 0.267 | 0.340 | 0.420 | 0.501 |
| CM48E3 | 0.027 | 0.054 | 0.098 | 0.157 | 0.215 | 0.289 | 0.362 | 0.449 | 0.537 |
| CM48E4 | 0.040 | 0.076 | 0.142 | 0.215 | 0.296 | 0.384 | 0.486 | 0.596 | - |
| CM59A4 | 0.040 | 0.076 | 0.142 | 0.215 | 0.296 | 0.384 | 0.486 | 0.596 | - |
| CM60A3 | 0.024 | 0.047 | 0.076 | 0.106 | 0.149 | 0.201 | 0.252 | 0.318 | 0.376 |
| CM60A4 | 0.024 | 0.047 | 0.076 | 0.106 | 0.179 | 0.230 | 0.296 | 0.362 | 0.435 |
| CM60B3 | 0.020 | 0.040 | 0.069 | 0.091 | 0.128 | 0.171 | 0.223 | 0.274 | 0.325 |
| CM60B4 | 0.040 | 0.076 | 0.113 | 0.157 | 0.201 | 0.267 | 0.340 | 0.420 | 0.501 |

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

**Phone:** 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

# CM SERIES

- UNCASED COPPER
- FOR MANUFACTURED HOMES
- UPFLOW / DOWNFLOW

| CM SERIES: DIMENSIONAL DATA (In.) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| COIL MODELS | Wet Coil Static Pressure Drop (in. w.c.) @ CFM | | | | | | | | |
| | 400 | 600 | 800 | 1000 | 1200 | 1400 | 1600 | 1800 | 2000 |
| CM24A2 | 0.113 | 0.181 | 0.318 | 0.489 | 0.671 | 0.887 | - | - | - |
| CM24A3 | 0.136 | 0.250 | 0.432 | 0.659 | 0.898 | - | - | - | - |
| CM24B2 | 0.079 | 0.125 | 0.238 | 0.363 | 0.511 | 0.671 | 0.853 | - | - |
| CM24B3 | 0.125 | 0.216 | 0.375 | 0.557 | 0.773 | - | - | - | - |
| CM24C2 | 0.057 | 0.130 | 0.171 | 0.264 | 0.368 | 0.493 | 0.617 | 0.762 | - |
| CM24C3 | 0.098 | 0.192 | 0.275 | 0.410 | 0.565 | 0.741 | - | - | - |
| CM24D2 | 0.047 | 0.109 | 0.130 | 0.212 | 0.295 | 0.399 | 0.503 | 0.617 | 0.741 |
| CM24D3 | 0.078 | 0.161 | 0.212 | 0.327 | 0.461 | 0.607 | 0.762 | - | - |
| CM30A2 | 0.057 | 0.109 | 0.192 | 0.295 | 0.420 | 0.544 | 0.690 | - | - |
| CM30A3 | 0.078 | 0.150 | 0.264 | 0.399 | 0.555 | 0.721 | - | - | - |
| CM30B2 | 0.057 | 0.130 | 0.171 | 0.264 | 0.368 | 0.493 | 0.617 | 0.762 | - |
| CM30B3 | 0.078 | 0.150 | 0.233 | 0.358 | 0.503 | 0.658 | 0.824 | - | - |
| CM30C2 | 0.047 | 0.109 | 0.130 | 0.212 | 0.295 | 0.399 | 0.503 | 0.617 | 0.741 |
| CM30C3 | 0.078 | 0.161 | 0.212 | 0.327 | 0.461 | 0.607 | 0.762 | - | - |
| CM36A2 | 0.047 | 0.098 | 0.150 | 0.233 | 0.327 | 0.430 | 0.544 | 0.679 | 0.814 |
| CM36A3 | 0.057 | 0.119 | 0.202 | 0.316 | 0.441 | 0.576 | 0.721 | - | - |
| CM36A4 | 0.078 | 0.161 | 0.285 | 0.420 | 0.586 | 0.773 | - | - | - |
| CM36B2 | 0.047 | 0.109 | 0.130 | 0.212 | 0.295 | 0.399 | 0.503 | 0.617 | 0.741 |
| CM36B3 | 0.057 | 0.130 | 0.192 | 0.285 | 0.399 | 0.534 | 0.669 | 0.824 | - |
| CM36B4 | 0.067 | 0.130 | 0.223 | 0.337 | 0.472 | 0.627 | 0.793 | - | - |
| CM36C3 | 0.047 | 0.109 | 0.171 | 0.233 | 0.337 | 0.441 | 0.555 | 0.690 | 0.824 |
| CM36E3 | 0.078 | 0.150 | 0.233 | 0.358 | 0.503 | 0.658 | 0.824 | - | - |
| CM36E4 | 0.109 | 0.202 | 0.327 | 0.482 | 0.669 | - | - | - | - |
| CM42A2 | 0.034 | 0.078 | 0.119 | 0.181 | 0.264 | 0.347 | 0.441 | 0.544 | 0.658 |
| CM42A3 | 0.047 | 0.098 | 0.161 | 0.254 | 0.347 | 0.461 | 0.586 | 0.721 | 0.876 |
| CM42A4 | 0.047 | 0.098 | 0.192 | 0.295 | 0.410 | 0.534 | 0.679 | 0.835 | - |
| CM48A3 | 0.034 | 0.078 | 0.130 | 0.202 | 0.285 | 0.389 | 0.493 | 0.607 | 0.721 |
| CM48A4 | 0.034 | 0.078 | 0.130 | 0.244 | 0.337 | 0.441 | 0.565 | 0.700 | 0.835 |
| CM48B3 | 0.029 | 0.067 | 0.109 | 0.171 | 0.244 | 0.327 | 0.410 | 0.513 | 0.617 |
| CM48B4 | 0.047 | 0.098 | 0.150 | 0.233 | 0.327 | 0.441 | 0.555 | 0.679 | 0.824 |
| CM48C3 | 0.031 | 0.067 | 0.112 | 0.140 | 0.203 | 0.276 | 0.348 | 0.439 | 0.530 |
| CM48C4 | 0.031 | 0.067 | 0.112 | 0.167 | 0.248 | 0.330 | 0.412 | 0.512 | 0.620 |
| CM48D3 | 0.027 | 0.058 | 0.094 | 0.140 | 0.176 | 0.239 | 0.303 | 0.375 | 0.457 |
| CM48D4 | 0.040 | 0.085 | 0.130 | 0.185 | 0.239 | 0.321 | 0.412 | 0.512 | 0.611 |
| CM48E3 | 0.029 | 0.067 | 0.130 | 0.212 | 0.295 | 0.399 | 0.503 | 0.627 | 0.752 |
| CM48E4 | 0.047 | 0.098 | 0.192 | 0.295 | 0.410 | 0.534 | 0.679 | 0.835 | - |
| CM59A4 | 0.047 | 0.098 | 0.192 | 0.295 | 0.410 | 0.534 | 0.679 | 0.835 | - |
| CM60A3 | 0.024 | 0.049 | 0.085 | 0.121 | 0.176 | 0.239 | 0.303 | 0.385 | 0.457 |
| CM60A4 | 0.024 | 0.049 | 0.085 | 0.121 | 0.212 | 0.276 | 0.357 | 0.439 | 0.530 |
| CM60B3 | 0.020 | 0.040 | 0.076 | 0.103 | 0.149 | 0.203 | 0.267 | 0.330 | 0.394 |
| CM60B4 | 0.040 | 0.085 | 0.130 | 0.185 | 0.239 | 0.321 | 0.412 | 0.512 | 0.611 |

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

**Phone:** 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com