DA/DC/DE SERIES

►ALUMINUM COIL
►UPFLOW / DOWNFLOW

DA/DC/DE SERIES: DIMENSIONAL DATA (In.)

COIL MODELS	Dry Coil Static Pressure Drop (in. w.c.) @ CFM								
	400	600	800	1000	1200	1400	1600	1800	2000
D(A/C/E)24A2	0.062	0.113	0.193	0.289	0.391	0.515	-	-	-
D(A/C/E)24A3	0.098	0.171	0.296	0.435	0.589	-	-	-	-
D(A/C/E)24A4	0.098	0.208	0.340	0.508	-	-	-	-	-
D(A/C/E)24B2	0.047	0.084	0.142	0.215	0.303	0.391	0.501	-	-
D(A/C/E)24B3	0.076	0.128	0.223	0.332	0.457	0.589	-	-	-
D(A/C/E)24B4	0.098	0.179	0.296	0.442	-	-	-	-	-
D(A/C/E)24C2	0.040	0.076	0.113	0.171	0.237	0.310	0.391	0.486	0.581
D(A/C/E)24C3	0.062	0.113	0.171	0.259	0.362	0.471	0.589	-	-
D(A/C/E)24C4	0.084	0.149	0.237	0.347	0.479	-	-	-	-
D(A/C/E)24D2	0.031	0.062	0.091	0.135	0.193	0.252	0.318	0.391	0.471
D(A/C/E)24D3	0.047	0.098	0.142	0.208	0.296	0.384	0.486	0.589	-
D(A/C/E)24D4	0.069	0.128	0.193	0.289	0.391	0.515	-	-	-
D(A/C/E)30A2	0.047	0.084	0.142	0.215	0.303	0.391	0.501	-	-
D(A/C/E)30A3	0.076	0.128	0.223	0.332	0.457	0.589	-	-	-
D(A/C/E)30A4	0.076	0.157	0.259	0.391	0.530	-	-	-	-
D(A/C/E)30B2	0.040	0.076	0.113	0.171	0.237	0.310	0.391	0.486	0.581
D(A/C/E)30B3	0.062	0.113	0.171	0.259	0.362	0.471	0.589	-	-
D(A/C/E)30B4	0.084	0.149	0.237	0.347	0.479	-	-	-	-
D(A/C/E)30C2	0.031	0.062	0.091	0.135	0.193	0.252	0.318	0.391	0.471
D(A/C/E)30C3	0.047	0.098	0.142	0.208	0.296	0.384	0.486	0.589	-
D(A/C/E)30C4	0.069	0.128	0.193	0.289	0.391	0.515	-	-	-
D(A/C/E)30D2	0.027	0.054	0.084	0.113	0.157	0.208	0.267	0.325	0.391
D(A/C/E)30D3	0.040	0.084	0.128	0.171	0.245	0.318	0.406	0.493	0.589
D(A/C/E)30D4	0.054	0.106	0.164	0.237	0.325	0.428	0.537	-	-
D(A/C/E)36A2	0.040	0.076	0.113	0.171	0.237	0.310	0.391	0.486	0.581
D(A/C/E)36A3	0.062	0.113	0.171	0.259	0.362	0.471	0.589	-	-
D(A/C/E)36A4	0.062	0.120	0.208	0.303	0.420	-	-	-	-
D(A/C/E)36B2	0.031	0.062	0.091	0.135	0.193	0.252	0.318	0.391	0.471
D(A/C/E)36B3	0.047	0.098	0.142	0.208	0.296	0.384	0.486	0.589	-
D(A/C/E)36B4	0.054	0.098	0.164	0.252	0.340	0.449	0.567	-	-
D(A/C/E)36C2	0.027	0.054	0.084	0.113	0.157	0.208	0.267	0.325	0.391
D(A/C/E)36C3	0.040	0.084	0.128	0.171	0.245	0.318	0.406	0.493	0.589
D(A/C/E)36C4	0.054	0.106	0.164	0.237	0.325	0.428	0.537	-	-
D(A/C/E)36D2	0.024	0.047	0.076	0.091	0.135	0.179	0.223	0.274	0.332
D(A/C/E)36D3	0.034	0.069	0.113	0.149	0.201	0.267	0.340	0.420	0.501
D(A/C/E)36D4	0.047	0.091	0.142	0.201	0.274	0.362	0.457	0.559	-
D(A/C/E)42A2	0.031	0.062	0.091	0.135	0.193	0.252	0.318	0.391	0.471
D(A/C/E)42A3	0.047	0.098	0.142	0.208	0.296	0.384	0.486	0.589	-
D(A/C/E)42A4	0.054	0.098	0.164	0.252	0.340	0.449	0.567	-	-
D(A/C/E)42B2	0.027	0.054	0.084	0.113	0.157	0.208	0.267	0.325	0.391
D(A/C/E)42B3	0.040	0.084	0.128	0.171	0.245	0.318	0.406	0.493	0.589
D(A/C/E)42B4	0.047	0.084	0.135	0.208	0.289	0.376	0.471	0.581	-

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

Continued... DA/DC/DE SERIES: DIMENSIONAL DATA (In.)									
COIL MODELS	Dry Coil Static Pressure Drop (in. w.c.) @ CFM								
	400	600	800	1000	1200	1400	1600	1800	2000
D(A/C/E)42C2	0.024	0.047	0.076	0.091	0.135	0.179	0.223	0.274	0.332
D(A/C/E)42C3	0.034	0.069	0.113	0.149	0.201	0.267	0.340	0.420	0.501
D(A/C/E)42C4	0.047	0.091	0.142	0.201	0.274	0.362	0.457	0.559	-
D(A/C/E)42D2	0.020	0.040	0.062	0.076	0.113	0.149	0.193	0.237	0.289
D(A/C/E)42D3	0.031	0.062	0.098	0.120	0.171	0.230	0.296	0.362	0.435
D(A/C/E)42D4	0.040	0.084	0.128	0.171	0.237	0.310	0.391	0.479	0.574
D(A/C/E)48A2	0.024	0.047	0.076	0.106	0.149	0.193	0.252	0.310	0.369
D(A/C/E)48A3	0.031	0.062	0.098	0.149	0.208	0.281	0.354	0.435	0.523
D(A/C/E)48A4	0.047	0.084	0.135	0.208	0.289	0.376	0.471	0.581	-
D(A/C/E)48B2	0.024	0.047	0.076	0.091	0.135	0.179	0.223	0.274	0.332
D(A/C/E)48B3	0.027	0.054	0.084	0.128	0.179	0.237	0.296	0.369	0.442
D(A/C/E)48B4	0.040	0.076	0.113	0.171	0.237	0.318	0.398	0.493	0.589
D(A/C/E)48C2	0.020	0.040	0.062	0.076	0.113	0.149	0.193	0.237	0.289
D(A/C/E)48C3	0.031	0.062	0.098	0.120	0.171	0.230	0.296	0.362	0.435
D(A/C/E)48C4	0.031	0.062	0.098	0.149	0.208	0.274	0.340	0.420	0.508
D(A/C/E)48D2	0.014	0.027	0.054	0.084	0.098	0.128	0.164	0.208	0.245
D(A/C/E)48D3	0.027	0.054	0.084	0.120	0.149	0.201	0.252	0.332	0.376
D(A/C/E)48D4	0.040	0.076	0.113	0.157	0.208	0.267	0.340	0.420	0.501
D(A/C/E)60A2	0.014	0.027	0.054	0.069	0.106	0.142	0.179	0.223	0.267
D(A/C/E)60A3	0.024	0.047	0.076	0.106	0.149	0.201	0.252	0.318	0.376
D(A/C/E)60A4	0.031	0.062	0.098	0.149	0.208	0.274	0.340	0.420	0.508
D(A/C/E)60B2	0.014	0.027	0.054	0.084	0.098	0.128	0.164	0.208	0.245
D(A/C/E)60B3	0.020	0.040	0.069	0.098	0.128	0.171	0.223	0.274	0.332
D(A/C/E)60B4	0.027	0.054	0.091	0.128	0.179	0.237	0.296	0.369	0.442
D(A/C/E)60C2	0.012	0.024	0.047	0.069	0.091	0.106	0.135	0.164	0.201
D(A/C/E)60C3	0.014	0.027	0.054	0.076	0.106	0.142	0.179	0.223	0.267
D(A/C/E)60C4	0.027	0.054	0.091	0.128	0.179	0.237	0.296	0.369	0.442
D(A/C/E)60D2	0.007	0.014	0.027	0.054	0.069	0.076	0.098	0.128	0.157
D(A/C/E)60D3	0.014	0.027	0.054	0.084	0.106	0.120	0.157	0.193	0.237
D(A/C/E)60D4	0.015	0.031	0.062	0.084	0.113	0.142	0.186	0.230	0.281

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

DA/DC/DE SERIES

►ALUMINUM COIL
►UPFLOW / DOWNFLOW

DA/DC/DE SERIES: DIMENSIONAL DATA (In.)

COIL MODELS	Wet Coil Static Pressure Drop (in. w.c.) @ CFM								
	400	600	800	1000	1200	1400	1600	1800	2000
D(A/C/E)24A2	0.079	0.159	0.284	0.432	0.591	0.784	-	-	-
D(A/C/E)24A3	0.136	0.250	0.443	0.659	0.898	-	-	-	-
D(A/C/E)24A4	0.136	0.307	0.511	0.773	-	-	-	-	-
D(A/C/E)24B2	0.056	0.113	0.204	0.318	0.454	0.591	0.762	-	-
D(A/C/E)24B3	0.102	0.181	0.329	0.500	0.693	0.898	-	-	-
D(A/C/E)24B4	0.136	0.261	0.443	0.671	-	-	-	-	-
D(A/C/E)24C2	0.047	0.098	0.150	0.233	0.327	0.430	0.544	0.679	0.814
D(A/C/E)24C3	0.078	0.150	0.233	0.358	0.503	0.658	0.824	-	-
D(A/C/E)24C4	0.109	0.202	0.327	0.482	0.669	-	-	-	-
D(A/C/E)24D2	0.034	0.078	0.119	0.181	0.264	0.347	0.441	0.544	0.658
D(A/C/E)24D3	0.057	0.130	0.192	0.285	0.410	0.534	0.679	0.824	-
D(A/C/E)24D4	0.088	0.171	0.264	0.399	0.544	0.721	-	-	-
D(A/C/E)30A2	0.056	0.113	0.204	0.318	0.454	0.591	0.762	-	-
D(A/C/E)30A3	0.102	0.181	0.329	0.500	0.693	0.898	-	-	-
D(A/C/E)30A4	0.102	0.227	0.386	0.591	0.807	-	-	-	-
D(A/C/E)30B2	0.047	0.098	0.150	0.233	0.327	0.430	0.544	0.679	0.814
D(A/C/E)30B3	0.078	0.150	0.233	0.358	0.503	0.658	0.824	-	-
D(A/C/E)30B4	0.109	0.202	0.327	0.482	0.669	-	-	-	-
D(A/C/E)30C2	0.034	0.078	0.119	0.181	0.264	0.347	0.441	0.544	0.658
D(A/C/E)30C3	0.057	0.130	0.192	0.285	0.410	0.534	0.679	0.824	-
D(A/C/E)30C4	0.088	0.171	0.264	0.399	0.544	0.721	-	-	-
D(A/C/E)30D2	0.029	0.067	0.109	0.150	0.212	0.285	0.368	0.451	0.544
D(A/C/E)30D3	0.047	0.109	0.171	0.233	0.337	0.441	0.565	0.690	0.824
D(A/C/E)30D4	0.067	0.140	0.223	0.327	0.451	0.596	0.752	-	-
D(A/C/E)36A2	0.047	0.098	0.150	0.233	0.327	0.430	0.544	0.679	0.814
D(A/C/E)36A3	0.078	0.150	0.233	0.358	0.503	0.658	0.824	-	-
D(A/C/E)36A4	0.078	0.161	0.285	0.420	0.586	-	-	-	-
D(A/C/E)36B2	0.034	0.078	0.119	0.181	0.264	0.347	0.441	0.544	0.658
D(A/C/E)36B3	0.057	0.130	0.192	0.285	0.410	0.534	0.679	0.824	-
D(A/C/E)36B4	0.067	0.130	0.223	0.347	0.472	0.627	0.793	-	-
D(A/C/E)36C2	0.029	0.067	0.109	0.150	0.212	0.285	0.368	0.451	0.544
D(A/C/E)36C3	0.047	0.109	0.171	0.233	0.337	0.441	0.565	0.690	0.824
D(A/C/E)36C4	0.067	0.140	0.223	0.327	0.451	0.596	0.752	-	-
D(A/C/E)36D2	0.024	0.057	0.098	0.119	0.181	0.244	0.306	0.378	0.461
D(A/C/E)36D3	0.039	0.088	0.150	0.202	0.275	0.368	0.472	0.586	0.700
D(A/C/E)36D4	0.057	0.119	0.192	0.275	0.378	0.503	0.638	0.783	-
D(A/C/E)42A2	0.034	0.078	0.119	0.181	0.264	0.347	0.441	0.544	0.658
D(A/C/E)42A3	0.057	0.130	0.192	0.285	0.410	0.534	0.679	0.824	-
D(A/C/E)42A4	0.067	0.130	0.223	0.347	0.472	0.627	0.793	-	-
D(A/C/E)42B2	0.029	0.067	0.109	0.150	0.212	0.285	0.368	0.451	0.544
D(A/C/E)42B3	0.047	0.109	0.171	0.233	0.337	0.441	0.565	0.690	0.824
D(A/C/E)42B4	0.057	0.109	0.181	0.285	0.399	0.524	0.658	0.814	

R51341 260220

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com

Continued... DA/DC/DE SERIES: DIMENSIONAL DATA (In.)									
COIL MODELS	Wet Coil Static Pressure Drop (in. w.c.) @ CFM								
	400	600	800	1000	1200	1400	1600	1800	2000
D(A/C/E)42C2	0.024	0.057	0.098	0.119	0.181	0.244	0.306	0.378	0.461
D(A/C/E)42C3	0.039	0.088	0.150	0.202	0.275	0.368	0.472	0.586	0.700
D(A/C/E)42C4	0.057	0.119	0.192	0.275	0.378	0.503	0.638	0.783	-
D(A/C/E)42D2	0.020	0.040	0.067	0.085	0.130	0.176	0.230	0.285	0.348
D(A/C/E)42D3	0.031	0.067	0.112	0.140	0.203	0.276	0.357	0.439	0.530
D(A/C/E)42D4	0.040	0.094	0.149	0.203	0.285	0.375	0.475	0.584	0.702
D(A/C/E)48A2	0.024	0.057	0.098	0.140	0.202	0.264	0.347	0.430	0.513
D(A/C/E)48A3	0.034	0.078	0.130	0.202	0.285	0.389	0.493	0.607	0.731
D(A/C/E)48A4	0.057	0.109	0.181	0.285	0.399	0.524	0.658	0.814	-
D(A/C/E)48B2	0.024	0.057	0.098	0.119	0.181	0.244	0.306	0.378	0.461
D(A/C/E)48B3	0.029	0.067	0.109	0.171	0.244	0.327	0.410	0.513	0.617
D(A/C/E)48B4	0.047	0.098	0.150	0.233	0.327	0.441	0.555	0.690	0.824
D(A/C/E)48C2	0.020	0.040	0.067	0.085	0.130	0.176	0.230	0.285	0.348
D(A/C/E)48C3	0.031	0.067	0.112	0.140	0.203	0.276	0.357	0.439	0.530
D(A/C/E)48C4	0.031	0.067	0.112	0.176	0.248	0.330	0.412	0.512	0.620
D(A/C/E)48D2	0.014	0.027	0.058	0.094	0.112	0.149	0.194	0.248	0.294
D(A/C/E)48D3	0.027	0.058	0.094	0.140	0.176	0.239	0.303	0.403	0.457
D(A/C/E)48D4	0.040	0.085	0.130	0.185	0.248	0.321	0.412	0.512	0.611
D(A/C/E)60A2	0.014	0.027	0.058	0.076	0.121	0.167	0.212	0.267	0.321
D(A/C/E)60A3	0.024	0.049	0.085	0.121	0.176	0.239	0.303	0.385	0.457
D(A/C/E)60A4	0.031	0.067	0.112	0.176	0.248	0.330	0.412	0.512	0.620
D(A/C/E)60B2	0.014	0.027	0.058	0.094	0.112	0.149	0.194	0.248	0.294
D(A/C/E)60B3	0.020	0.040	0.076	0.112	0.149	0.203	0.267	0.330	0.403
D(A/C/E)60B4	0.027	0.058	0.103	0.149	0.212	0.285	0.357	0.448	0.539
D(A/C/E)60C2	0.012	0.024	0.049	0.076	0.103	0.121	0.158	0.194	0.239
D(A/C/E)60C3	0.014	0.027	0.058	0.085	0.121	0.167	0.212	0.267	0.321
D(A/C/E)60C4	0.027	0.058	0.103	0.149	0.212	0.285	0.357	0.448	0.539
D(A/C/E)60D2	0.007	0.014	0.027	0.058	0.076	0.085	0.112	0.149	0.185
D(A/C/E)60D3	0.014	0.027	0.058	0.094	0.121	0.140	0.185	0.230	0.285
D(A/C/E)60D4	0.015	0.031	0.067	0.094	0.130	0.167	0.221	0.276	0.339

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2026 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com