NOMENCLATURE

ASPEN UNIVERSAL COIL SERIAL NUMBER

D A 24 A3 D -145 L -400

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

⑧ OPTION CODE

⑦ LOCATION OF REFRIGERANT & PLUMBING CONNECTIONS

- **L** = Left-hand
- **R** = Right-hand
- **T** = Refrigerant out the top, plumbing out opposite sides

⑥ WIDTH CODE

EXAMPLE(S): 130 = 13", 145 = 14.5", 160 = 16", 195 = 19.5", 245 = 24.5", etc.

- **DRAIN PAN:** CA, DA, CM, & DM Series
- **FURNACE:** CC, CE, CP, CX, DC, DE, DP, & DX Series

⑤ METERING DEVICES

A2L (R32 / R454B) REFRIGERANTS

D = Non-Bleed A/C or H/P R32 TXV
J = Non-Bleed A/C or H/P R454B TXV
K = 20% Bleed A/C or H/P R454B TXV
M = R32 Piston
N = R454B Piston
Z = R454B or R32 CONFIGURABLE (Shipped w/ R454B Piston)

A1 (R22 / R410A) REFRIGERANTS

4 = Non-Bleed A/C or H/P R410 TXV
X = Non-Bleed A/C or H/P R22 TXV
B = 20% Bleed A/C or H/P R22 TXV
6 = 20% Bleed A/C or H/P R410 TXV
F = R22 Piston
G = R410A Piston

④ COIL DESCRIPTOR CODE

- **LETTER**: Face area, FPI
- **NUMBER OF ROWS:** 2-4

③ NOMINAL TONNAGE (MBTUH)

18 = 18,000 **24** = 24,000 **30** = 30,000 **36** = 36,000 **42** = 42,000 **48** = 48,000 **60** = 60,000 etc.

② CONFIGURATION

A = Uncased up/down
C = Cased up/down
E = Cased multi-position VersaCoil
M = Manufactured home coil
H = Cased dedicated horizontal slab coil
P = Cased dedicated horizontal with attached plenum
X = Cased dedicated horizontal coil

① SERIES

C = C Series (Copper)
D = D Series (Aluminum)

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website.

Phone: 281.441.6500 **Toll Free:** 800.423.9007 **Fax:** 281.441.6510 **Customer Service:** info@aspenmfg.com **Warranty Team:** warranty@aspenmfg.com